

SpillProtec[™]

Oil Absorbent Pad










SpillProtec Oil absorbent pads are designed to absorb oil and oil-based liquids only that are dripped, leaked & spilled.



Applications

- Up Stream & Down Stream operations
- Maintenance Hangers
- Factory floor
- Manufacturing & Assembly
- Repair facilities & Body Shops
- Event Centres & Cinemas
- Theme Parks
- Substations

Industries

-  Oil & Gas
-  Aviation
-  Heavy Engineering
-  Food
-  Automotive
-  Warehousing
-  Power
-  Metals & Mining
-  Hospitality & Events

Available Models

Model	OAPD2144	OAPD4108	OAPD5144
Material	Polypropylene	Polypropylene	Polypropylene
Color	White	White	White
Size	40 x 50 (CM)	40 x 50 (CM)	40 x 50 (CM)
Thickness	2 MM	4 MM	5 MM
Absorption capacity	144 L	108 L	144 L
Pieces / Carton	200	100	100
Carton Dimension	42x52X42CM	42x 52X32CM	42x52X42CM
Carton Weight	8 kg / 17.63 lbs	6 kg / 13.22 lbs	8 kg / 17.63 lbs
Product SKU	BLSH-OAPD2144	BLSH-OAPD4108	BLSH-OAPD5144
Carton GTIN	00810148530631	00810148530648	00810148530655

Storage

Store the absorbents in a clean and dry area, away from direct sunlight.

Disposal

Dispose of used absorbents in accordance with both local and national regulations.